

STYLE-902

Expanded Graphite packing with corrosion inhibitor, has a very low friction, does not damage shaft or stems. High Thermal Conductivity and chemical resistance and

Application Areas: STYLE-902 Can be used in valves, pumps, mixers and agitators in high pressure, power stations, boiler houses, and in the Chemical Industries.

PRECAUTION- Highly oxidizing agents.



Benefits: STYLE-902 is suitable for a wide range of applications & can reduce stock inventories considerably, provide economic alternatives to asbestos packings, reduce maintenance time. Style-902 yields more meters per kg. which makes it very economical.

SERVICE LIMITS

	Rotating	Reciprocating	Static
Pressure	20 bar	95 bar	285 bar
Shaft speed	20m/s		
Density	1.0 g/cm ³		
Temperature	-220 +450°C (+650°C with Steam) 1000°C inert gas.		
PH Range	0~14		

All Technical data and recommendations given are based on our experience. However, we do not undertake any liability whatsoever. All data and values have to be checked by the user, since the effectiveness of a seal can only be judged correctly by evaluating all data parameters directly on site. The stated parameters of all packing styles are approximate and may be influenced if occurring together. We suggest you contact us in the case of special applications.

120, Raj Prabha Land Mark Industrial Estate, 1st Floor, Building no. 3, Gokhivare Village, Bhoidapada, Vasai (E), Dist. Thane - 401 208.

ePTFE Gaskets & Sheets • Gland Packing • Non Asbestos Gaskets & Sheets • Metallic Gaskets and other Sealing Products

Tel.: 0250 6093377 Mob-09920168285 / 09821152367 Email : admin@sealmax.net / sales@sealmax.net Web : www.sealmax.in