

STYLE-927

Material composition: Braided from Expanded PTFE graphited yarn .The packing is soft. There are no free particles of graphite on surface and therefore no contamination can occur.

Application : Used in pumps, valves, mixers and agitators. Style-927 is well suited for service involving high peripheral speeds and temperatures, where pure PTFE packing fail. Can be safely used in all chemical pump applications with the exception of molten alkali metals, fluoride nitric acid and other strong oxidizing agents.



Benefits: Because of its extremely wide application range, successfully replace many other packings and reduce stock levels considerably.

SERVICE LIMITS

	Rotating	Reciprocating	Static
Pressure	25 bar	100 bar	200 bar
Shaft speed	20 m/s		
Density	1.5 ~1.6 g/cm ³		
Temperature	-200 +280 Deg.C		
PH Range	0~14		

All Technical data and recommendations given are based on our experience. However , we do not undertake any liability whatsoever, All data and values have to be checked by the user, since the effectiveness of a seal can only be judged correctly by evaluating all data parameters directly on site. The stated parameters of all packing styles are approximate and may be influenced if occurring together. We suggest you contact us in the case of special applications.

120, Raj Prabha Land Mark Industrial Estate, 1st Floor, Building no. 3, Gokhivare Village, Bhoidapada, Vasai (E), Dist. Thane - 401 208.

ePTFE Gaskets & Sheets • Gland Packing • Non Asbestos Gaskets & Sheets • Metallic Gaskets and other Sealing Products

Tel.: 0250 6093377 Mob-09920168285 / 09821152367 Email : admin@sealmax.net / sales@sealmax.net Web : www.sealmax.in