




KERAM.

Cords, Packings & Tapes.

PROPERTIES

- Aluminium silicate fiber products reinforced with chromium steel wire
- 15-20 % organic carrier fibers
- Resistant to oils, greases, and chemicals except hydrofluoric acid, phosphoric acid, and strong bases
- The organic components disintegrate at approx. 200 °C, stability decreases
- Smoke development or short flare-up at initial high temperature load
- Continuous operating temperature: 1100 °C
- Static sealing system for kilns, boilers, vessels, etc.

Product designation	Keram cord	Keram packing
Product No.	0905	0910
Product image		
Features	<ul style="list-style-type: none"> • Round twisted • Additional treatments/waterproofing: Graphite, PTFE, vermiculite, glimmer, silicon • Dimensions: Ø 4-50 mm [other dimensions on request] 	<ul style="list-style-type: none"> • Square braiding • Additional treatments/waterproofing: Graphite, PTFE, vermiculite, glimmer, silicon • Dimensions: 5-90 mm vkt. [other dimensions on request]
Product designation	Keram tape	
Product No.	0930	
Product image		
Features	<ul style="list-style-type: none"> • Fabric with rigid edges • Additional treatments/waterproofing: Graphite, PTFE, vermiculite, glimmer, silicon • Dimensions: Thicknesses: 3 & 5 mm Widths: 20-100 mm [other dimensions on request] 	