

## STYLE-915F

Braided from 100% pure multi filament PTFE yarn impregnated with PTFE dispersion. Very supple packing with High Density and Flexibility. Fast and simple to install,

STYLE-915F ideal for nearly all-even the most aggressive media. Suitable for Pharmaceutical and food applications.



**BENEFITS:** Resistant to nearly all fluids & gases including the most corrosive acids and alkalis. Universal valve packing with long packing life. Conforms to FDA regulations for use with foodstuffs, potable water and pharmaceutical products.

### SERVICE LIMITS

	Rotating	Reciprocating	Static
<b>Pressure</b>	20 bar	150 bar	250 bar
<b>Shaft speed</b>	10 m/s		
<b>Density</b>	1.6 g/cm <sup>3</sup>		
<b>Temperature</b>	-200 +280 Deg.C		
<b>PH Range</b>	0~14		

All Technical data and recommendations given are based on our experience. However, we do not undertake any liability whatsoever. All data and values have to be checked by the user, since the effectiveness of a seal can only be judged correctly by evaluating all data parameters directly on site. The stated parameters of all packing styles are approximate and may be influenced if occurring together. We suggest you contact us in the case of special applications.

120, Raj Prabha Land Mark Industrial Estate, 1st Floor, Building no. 3, Gokhivare Village, Bhoidapada, Vasai (E), Dist. Thane - 401 208.

ePTFE Gaskets & Sheets • Gland Packing • Non Asbestos Gaskets & Sheets • Metallic Gaskets and other Sealing Products

Tel.: 0250 6093377 Mob-09920168285 / 09821152367 Email : [admin@sealmax.net](mailto:admin@sealmax.net) / [sales@sealmax.net](mailto:sales@sealmax.net) Web : [www.sealmax.in](http://www.sealmax.in)