

STYLE-916

Braided From 100% pure expanded PTFE yarn, lubricated with silicone oil. Very malleable packing with low coefficient of friction, does not wear shafts, excellent chemical resistance. Easy to Install, needs little gland adjustment.

STYLE-916 pure PTFE Packing suitable for use with nearly all fluids, including the most corrosive acids and alkalis.



BENEFITS: Extremely low Coefficient of friction of PTFE gives this packing excellent life.

SERVICE LIMITS

	Rotating	Reciprocating	Static
Pressure	30 bar	30 bar	200 bar
Shaft speed	11 m/s		
Density	1.6 g/cm ³		
Temperature	-100 +280 Deg.C		
PH Range	0~14		

All Technical data and recommendations given are based on our experience. However, we do not undertake any liability whatsoever. All data and values have to be checked by the user, since the effectiveness of a seal can only be judged correctly by evaluating all data parameters directly on site. The stated parameters of all packing styles are approximate and may be influenced if occurring together. We suggest you contact us in the case of special applications.

120, Raj Prabha Land Mark Industrial Estate, 1st Floor, Building no. 3, Gokhivare Village, Bhoidapada, Vasai (E), Dist. Thane - 401 208.

ePTFE Gaskets & Sheets • Gland Packing • Non Asbestos Gaskets & Sheets • Metallic Gaskets and other Sealing Products

Tel.: 0250 6093377 Mob-09920168285 / 09821152367 Email : admin@sealmax.net / sales@sealmax.net Web : www.sealmax.in