




THERMOTOP®.

Cords, Packings & Tapes.

PROPERTIES

- Textured, modified glass fiber products without organic carrier fibers
- Soft, supple, skin-friendly, non-flammable, impervious to moisture
- Resistant to fumes, oils, and most bases and acids
- Continuous operating temperature: 750 °C
- Shrinks by only approx. 2% at max. permissible temperature load
- Static sealing system against dry heat in kilns, boilers, vessels, etc.

Product Name	Thermotop® cord	Thermotop® packing
Product No.	0805	0810
Features		
Characteristics	<ul style="list-style-type: none"> • Round twisted • Additional treatments/waterproofing: Graphite, PTFE, vermiculite, glimmer, silicon • Dimensions: Ø 3–30 mm [other dimensions on request] 	<ul style="list-style-type: none"> • Square braiding • Additional treatments/waterproofing: Graphite, PTFE, vermiculite, glimmer, silicon • Dimensions: Ø 5–90 mm vkt. [other dimensions on request]

Product Name	Thermotop® tape
Product No.	0830
Product Image	
Features	<ul style="list-style-type: none"> • Fabric with rigid edges • Additional treatments/waterproofing: Graphite, PTFE, vermiculite, glimmer, silicon • Dimensions: Thicknesses: 3 & 5 mm Widths: 20–100 mm [other dimensions on request]